




1/24

Fig. 1



200501-602200T



2/24




Fig. 2

10072703.101002

200701-8022001



TITLE: High-Intensity Lighting Fixture
 FILED: Gordin, et al.
 ATTY. DKT. # P04723US1
 Atty. Hansing - 515-288-3667

4/24

PART #	DESCRIPTION
18	.125 THK. ALUM. 5052-H32
134L&R	.100 THK. ALUM. 5052-H32, ANODIZE PER MIL SPEC MIL-A-8625F, TYPE II, CLASS I, CLEAR, LIGHT ETCH.
202	.020 THK. PREANODIZED ALUM. (REFLECTOR SHEET) OVERLAP (3") TEFLON TAPE OVER END AND TRIM W/ SCISSORS, 99% PTFE. TEFLON, GRADE: MILITARY, TEMP RANGE: -400°-+500°F, WIDTH: 1.50, THICKNESS: .003, ELONGATION: 50% MIN., SPEC. GRAVITY: 0.90 G/CC, COLOR: WHITE, SPECS. MEETS MILITARY SPEC. T-277-30A.
204	.080 THK. ALUM. 5052-H32
206	.060 ALUM. 5952-H32
208	.030 THK. ALUM. 5052-H32, STAINLESS STEEL 302 SPRING TEMPER
210	.060 THK. ALUM. 5052-H32
300	.060 THK. ALUM.

Fig. 3B



5/24




Fig. 4




Fig. 5

.015 THK. 300 SERIES
SS FULL HARD TEMPER
ROCKWELL C40-45.
(PASSIVATE PER
ASTM A 380)

200701-80224001



6/24




Fig. 6A

200701*0022001



TITLE: High-Intensity Lighting Fixture
FILED: Gordin, et al.
ATTY. DKT. # P04723US1
Atty. Hansing - 515-288-3667

7/24





Fig. 6B

200701-EO/22001



8/24



COATING MUST BE CENTERED
±5° WHEN LAMP IS PLACED
INTO LAMP HOLDERS

Fig. 6C

10072703-104002

O I P E J C 5 9
 OCT 10 2002
 DATE: 3/10/02

9/24

ORIENTATE THE 120° REFLECTIVE COATING
 OFF OF THIS END OF LAMP ONLY.
 PINCH SEALS ARE NOT ALWAYS IN LINE
 WITH EACH OTHER.




Fig. 7A

LAMP LOCATOR WILL LOCATE
 OFF OF CERAMIC HOLDER AND
 SIDES OF PINCH SEAL





Fig. 7B


$30^{\circ} \pm 10^{\circ}$



WHITE ALUM. OXIDE APPLIED
 BY LAMP MANUFACTURER.

DIELECTRIC DICHROIC REFLECTIVE
 COATING - SEE NOTES

Fig. 7C





10/24

NOTES:

1. REFLECTIVE COATED PARTS SHALL HAVE A TRANSMISSION AT NORMAL INCIDENCE OF LESS THAN 1% AVERAGE FROM 400NM TO 700 NM, AND GREATER THAN 70% AVERAGE TRANSMISSION AT NORMAL INCIDENCE FROM 800NM TO 1500NM. COATING SHALL BE DESIGNED FOR GREATER THAN 90% REFLECTION FROM 400NM TO 700NM.
2. REFLECTIVE COATING SHALL SURVIVE RAPID THERMAL SHOCK TO 900 DEGREES C. THIS SHALL BE TESTED FOR BY INSERTION OF A COATED WITNESS PLATE INTO A TEST CHAMBER HELD AT 900 DEGREES C; HOLDING THE WITNESS AT ROOM TEMPERATURE FOR 30 MINUTES, AND RAPID WITHDRAWAL OF THE WITNESS TO ROOM TEMPERATURE. THE COATING ON THE WITNESS PLATE SHALL SURVIVE THIS TEMPERATURE CYCLE WITH NO LOSS OF COATING.
3. REFLECTIVE COATING SHALL SURVIVE STANDARD 24 HOUR HUMIDITY TEST AT 49 DEGREES C. AND PASS QUICK TAPE TEST.
4. FILM CRACKING AND CRYSTALLIZATION OF THE REFLECTIVE COATING SHALL BE ACCEPTABLE, PROVIDED THAT NO COATING VOID SHALL BE LARGER THAN 0.010 INCHES IN ITS LARGEST DIMENSION.
5. COAT 360 DEGREES OF THE ARC TUBE WITH UV BLOCKING FILM. THE UV BLOCKING SHALL PRODUCE A COATING DESIGNED TO HAVE $T < OR = 1\%$ AVERAGE FROM 200NM TO 390NM WHILE MAINTAINING $T > OR = 95\%$ AVERAGE IN THE VISIBLE, APPROXIMATELY 400NM TO 700NM. THE FILM MUST WITHSTAND LONG TERM EXPOSURE TO APPROXIMATELY 1000° C.

Fig. 7E

10072703.101002

200T01* E022/001



TITLE: High-Intensity Lighting Fixture
FILED: Gordin, et al.
ATTY. DKT. # P04723US1
Atty. Hansing - 515-288-3667

11/24




Fig. 8A




Fig. 8B




Fig. 8C



Fig. 8D

- NOTE:
1. DIMENSIONS IN () ARE INCHES.
 2. DIMENSION IS THE ARC LENGTH.
 3. PENNSYLVANIA LAMP NUMBER M2000T9/DE



12/24

200701" E022200T




Fig. 9B




Fig. 9C




Fig. 9A




Fig. 9D



200T01-EO/2200T




Fig. 10A




Fig. 10B




Fig. 10E




Fig. 10C




Fig. 10D

13/24

200101" 80/22001

TITLE: High-Intensity Lighting Fixture
FILED: Gordin, et al.
ATTY. DKT. # P04723US1
Atty. Hansing - 515-288-3667



14/24





Fig. 11A



DETAIL B

Fig. 11C





Fig. 11B



SECTION: A-A

Fig. 11E




Fig. 11D



15/24





Fig. 12A



SECTION: A

Fig. 12B




Fig. 12C

200701-EO/22/001



16/24




Fig. 12D




Fig. 12E

Fig. 12F

10072703-101002

30703 in 1970




Fig. 13A



18/24




Fig. 13B

10072703-101002



19/24




Fig. 13C

NOTE:

1. NO FINGER PRINTS OR FOREIGN MATTER ON MIRROR.
USE WHITE COTTON GLOVES WHEN ASSEMBLING.
2. DO NOT ATTEMPT TO CLEAN MIRROR.

200701" 0022001



20/24





Fig. 13D

10072703-104002

200101" E022/001



TITLE: High-Intensity Lighting Fixture
FILED: Gordin, et al.
ATTY. DKT. # P04723US1
Atty. Hansing - 515-288-3667



- NOTE:
1. COATING: DICHROIC COLD COATING WITH A REFLECTANCE OF >94% FROM 430-680 NM.
 2. CURVATURE IS A 3-5/16" FOCAL LENGTH PARABOLA.

Fig. 13E



TITLE: High-Intensity Lighting Fixture
FILED: Gordin, et al.
ATTY. DKT. # P04723US1
Atty. Hansing - 515-288-3667

22/24




Fig. 13F

10072703-101002



23/24

"X" RAD	"Y" DIM
.911	.063
1.287	.125
1.576	.188
1.820	.250
2.035	.313
2.229	.375
2.408	.438
2.574	.500
2.730	.563
2.878	.625
3.018	.688
3.152	.750
3.281	.813
3.405	.875
3.524	.938
3.640	1.000
3.752	1.063
3.861	1.125
3.967	1.188
4.070	1.250
4.170	1.313
4.268	1.375
4.364	1.438
4.453	1.497

Fig. 13G

10072703.101002



10072703-104002




Fig. 13H